



				Target Applications					Advanced Features				
Product	Supported Standards	Supported Bands	Supported Interfaces	Cellular Devices	PMP/PND/MP-4	PC, Tablet & Smartphone Accessories	Set-Top-Box HDTV	Automotive Infotainment Devices	Embedded Conditional Access (CA)	Direct Connectivity to CA	MRC Diversity	USB Mass-Storage (UMS)*	Package (mm)
Global Multi-Standard													
SMS1130/ SMS1130T	- DVB-H/T (SMS1130) - T-DMB, DAB, DAB+ DAB V.2 - ISDB-T 1/3-Seg	170-240MHz 470-862MHz 1450-1492MHz 1660-1685MHz	- USB 2.0 HS - SPI, SDIO - CPU Parallel Bus - Serial (I²C-like) Control - TS	☑	☑	☑	—	—	—	—	—	—	BGA 6.2x6.5x0.9
SMS1140	- DVB-T - T-DMB, DAB, DAB+ DAB V.2 - ISDB-T 1/3-Seg	170-240MHz 470-862MHz	- USB 2.0 HS - SPI, SDIO - CPU Parallel Bus - Serial (I²C-like) Control - TS	☑	☑	☑	—	—	—	—	☑	☑	BGA 10x10x1.0
 SMS1240	- DVB-T - T-DMB, DAB, DAB+ DAB V.2 - ISDB-T 1/3-Seg, sb	87.5-108MHz 470-862MHz	- USB 2.0 HS - SPI, SDIO - Serial (I²C-like) Control - TS	—	—	—	—	☑	—	—	☑	☑	BGA 10x10x1.0
SMS2230	- DVB-T/H - T-DMB, DAB, DAB+, DAB V.2 - ISDB-T: 1-Seg, sb - FM Radio with RDS	64-240 MHz 470-862 MHz	- USB 2.0 HS - SPI, SDIO - CPU Parallel Bus - Serial (I²C-like) Control - TS	☑	☑	☑	—	—	—	—	—	☑	BGA** 9.0x9.0x0.9
SMS2270	- DVB-T/H - T-DMB, DAB, DAB+, DAB V.2 - ISDB-T: Full-Seg, 1/3-Seg, sb, mm - Ginga SW - FM Radio with RDS	64-240 MHz 470-862 MHz	- USB 2.0 HS 2xSPI, SDIO - CPU Parallel Bus - Serial (I²C-like) Control - TS	—	☑	☑	☑	☑	—	—	☑	☑	BGA** 9.0x9.0x0.9
China CMMB													
 SMS1180	CMMB	470-862MHz 2100-2700MHz	- USB 2.0 HS - SPI, SDIO - CPU Parallel Bus - Serial (I²C-like) Control - TS	☑	☑	☑	—	☑	—	☑	☑	—	BGA 6.6x6.9x0.9
SMS1184	CMMB	470-862MHz	- USB 2.0 HS - SPI, SDIO - Serial (I²C-like) Control - TS	☑	☑	☑	—	—	—	☑	—	—	BGA 10x10x1.1
SMS1186	- CMMB - MBBMS SW	470-862MHz 2100-2700MHz	- USB 2.0 HS - SPI, SDIO - CPU Parallel Bus - Serial (I²C-like) Control - TS	☑	☑	—	—	—	☑	—	☑	—	BGA 6.6x6.9x0.9
SMS2186/ SMS2186D	- CMMB - MBBMS SW	470-862MHz	- SPI, SDIO - CPU Parallel Bus - Serial (I²C-like) Control - TS	☑	☑	—	—	—	☑	—	—	—	BGA 5.9x5.9x0.9
Latin America & Japan ISDB-T													
SMS2130	- ISDB-T 1-Seg - Ginga SW	470-862MHz	- SPI, SDIO - CPU Parallel Bus - Serial (I²C-like) Control - TS	☑	☑	☑	—	—	—	—	—	—	BGA 5.0x5.0x0.9
North America ATSC-M/H													
SMS1530	- ATSC-A/153 - FM Radio with RDS	54 -240MHz 470-806MHz	- SPI, SDIO - Serial (I²C-like) Control - TS	☑	☑	☑	—	☑	—	☑	—	—	BGA 7.0x7.0x0.9

(*) Siano's receivers enhanced with UMS enable direct management of on-board storage devices
 (**) Pin-to-pin and size compatible

Specifications are subject to change without prior notice.
 The Siano name and logo are registered trademarks of Siano Mobile Silicon Ltd. Siano enabling TV EVERYWHERE is a trademark of Siano Mobile Silicon Ltd. All other trademarks are the property of their respective holders.